



କାନ୍ତିରାମ

۲۷۰





2. **فَمَنْ لَمْ يَرْجِعْ إِلَيْنَا فَمَا كُنَّا نَعْلَمُ** **فَرَبِّ الْعِزَّةِ فَرَبِّ الْمُرْسَلِينَ** **فَمَنْ يَعْلَمُ**

## Minimum requirements

## **Item 01: Wireless Keyboard & Mouse Combo**

**Quantity:** 3

**Warranty:** Minimum 06 months

Specification	Description / Features
Keyboard	
Size	Full Size
Keyboard Technology	Scissors
Illumination	Backlight Key Illumination
Compatibility	Windows, macOS, Linux
Power	Rechargeable Battery, USB C
Wireless Receiver	USB wireless receiver
Interface	2.4 GHz, Bluetooth 5.1
Features	Quiet typing, Collaboration keys, Programmable keys, Numeric keypad
Mouse	
DPI	800-8000
Buttons	7
Wheels	Middle Scroll
Compatibility	Windows, macOS, Linux
Power	Rechargeable Battery, USB C
Wireless Receiver	USB wireless receiver
Interface	2.4 GHz, Bluetooth 5.1





### Item 02: POE Network Switch

**Warranty:** Minimum 6 Month

**Quantity:** 4

**Authorization Letter:** Required

Specification	Description / Features
Enclosure material	SGCC steel
Networking interface	(12) 10/100/1,000 MbE RJ45 ports (12) 100/1,000/2,500 MbE RJ45 ports
Management interface	Ethernet In-Band
SFP+ interface	(2) 10G SFP+ ports
PoE interface	(24) PoE/PoE+ (Pins 1, 2+; 3, 6-)
Total non-blocking throughput	62 Gbps
Switching capacity	124 Gbps
Forwarding rate	92.25 Mpps
Max. power consumption	550W
Power method	(1) Universal AC input, 100—240V AC, 8.5A Max., 50/60 Hz (1) USP-RPS DC input: 52V DC, 7.7A; 11.5V DC, 8.7A
Power supply	AC/DC, internal, 550W
Max. PoE+ wattage per port by PSE	34.2W
PoE budget	400W
Voltage range PoE mode	44— 57V
Voltage range PoE+ mode	50—57V
Services	SMB Layer 3 PoE GbE switch
ESD/EMP protection	Air: $\pm$ 16kV, contact: $\pm$ 12kV
LCM display	(1) 1.3" LCM color touchscreen Bootup animation: bootup in progress Firmware upgrade icon: firmware upgrading
Button	Factory reset
Operating temperature	-5 to 40° C (23 to 104° F)
Operating humidity	10 to 95% noncondensing
Certifications	CE, FCC, IC
Support	Unifi Devices and Gateways

### Item 03: Laptop Stand

**Quantity:** 25

Specification	Description / Features
Heigh Adjustment	2" – 3"
Material	Vegan Leather, Fiberglass
Comptible Model	11.6" – 16"
Weight	3oz
Dimension	180mm x 250mm x 3mm





#### **Item 04: Cordless Screwdriver**

**Quantity:** 2

Specification	Description / Features
Torque (soft/hard/max.)	-/5/- Nm
No-load speed (1st gear / 2nd gear)	0 – 360 rpm
Battery voltage	3.6 V
Battery type	Lithium-Ion
Chuck capacity, min./max.	6.35 mm
Clutch torque	0.2 - 5 Nm
Max. screw diameter	5 mm
Sound power level	80 dB(A)
Sound pressure level	70 dB(A)

## Item 05: Battery Tester

**Quantity:** 1

Specification	Description / Features
Testing Range	C, AA, AAA, D, N, 9V (6F22), and 1.55V button battery
Working Temperature	0°C ~ 40°C
Portable	Yes
Can Test	C, AA, AAA, D, N, 9V 6F22, and 1.5V button cell batteries

## Item 06: Micro Cleaning Tools Computer Vacuum/Blower Duster

**Quantity: 1**

Specification	Description / Features
Construction	All Steel
Speed	Single Speed
Motor	.75 Peak HP Single Fan Motor 220V
Amps	4.0
Watts	480
CFM	51
Cord	12 Ft. 2 Conductor
Unit Size	4" x 5.5" x 16"
Unit Weight	1.3 Kgs
ESD Safe	No
Accessories	20" Flexible Hose, Crevice Tool, Air "Pin Pointer", Dust Brush, Shoulder Strap, Five Extra Disposable Bags, plus 4 Pc. Micro Cleaning Tool Kit.





### Item 07: CCTV Tester

**Quantity:** 1

**Warranty:** Minimum 06 months

Specification	Description / Features
CPU/RAM/ROM	4-core 2.0GHz/2GB(LPDDR4)/16GB(EMMC)
Operating System	Android 11.0/+
Display	8-inch IPS touch screen, 2048*1536 resolution, Backlit buttons
IP Camera Test Max 8K 32MP	IP Discovery/ONVIF/IPC test /RTSP play /Client APK Rapid Video, Auto view the video, create testing report Hik test tool, pressing just one key to activate hikvision camera, Image test, can modify the username, password and IP parameters Dahua test tool, Dahua camera test, modify the username, password and IP parameters
IP& CVBS Test	IP& CVBS test at the same time, converter test from analog to digital with dual test window
Coaxial HD Test	8MP TVI camera test, 3840 x 2160P 15FPS, UTC control/call OSD menu, Support coaxial audio 8MP CVI camera test, 3840 x 2160P 12.5F/15F, UTC control/call OSD menu 8MP AHD camera test, 3840 x 2160P 15FPS, UTC control/call OSD menu 8MP EX-SDI, HD-SDI, 3G-SDI camera test, UTC control & call OSD menu
HDMI Input	1 channel HDMI input, support 4K 3840x2160P 30fps
HDMI Output	1 channel HDMI output, support 4K 3840x2160P 60fps
Zoom Image	4x zoom, to enlarge image, screen snapshot, record, save, view and record and play back
Power Supply	DC12V/2A
Wi-Fi	Built in WIFI, 2.4GHz and 5GHz, speeds:433Mbps
Network interface	RJ45 Dual Gigabit Ethernet ports, 10/100/1000Mbps adaptive
Network test	Trace route, Link monitor, DHCP server, port flashing, Ping test
Audio test	1 channel audio signal input, test whether sound normal, 1 channel audio signal, to connect headphone
Rechargeable	After charging 3 to 4 hours, normal working time 15 hours
Auto off	1 to 30(mins)
Dimension/Weight	Tester: 260x183x43mm(10.23x7.2x1.69inch) / 1200g(2.65lbs) Package: 350x300x100mm(13.78x11.81x3.94) / 2740g(6.04lbs)

### Item 08: RJ45 Crimping Tool

**Quantity:** 2

Specification	Description / Features
Pass Through Type	RJ45 Crimp Tool Pass Through CAT5 CAT5E CAT6 Crimper Cutter Stripper for RJ45 RJ12 RJ11 8P 6P End Pass Through connector





**Item 09: Pass Through RJ45 Jack 100PCS (Box or Pack)**

**Quantity:** 2

Specification	Description / Features
Pass Through RJ45 Jack 100PCS (Box or Pack)	Pass Through RJ45 Jacks (per Box or Pack should have at least 100PCS)

**Item 10: Shear Cutter**

**Quantity:** 2

Specification	Description / Features
Shear Cutter	Mult-Purpose shear cutter (with safety lock)



**Item 11: Wire Stripper**

**Quantity:** 4

Specification	Description / Features
Wire Stripper	Wire Stripper Tool



**Item 12: Networking Probe Kit**

**Quantity:** 1

**Warranty:** Minimum 03 months

Specification	Description / Features
Networking Probe Kit	Network toner and Probe kit Wire tracking RJ11 > 3000m; RJ45 > 100m, Low battery indication, 1050mAh rechargeable lithium battery.







**Item 19: Combination plier**

**Quantity:** 1

Specification	Description / Features
Combination Plier	Combination plier

**Item 20: Long nose plier**

**Quantity:** 4

Specification	Description / Features
Long nose plier	<p><b>Pliers Head Shape</b> Serrated</p> 

**Item 21: Wireless mini screwdriver set**

**Quantity:** 1

Specification	Description / Features
Mini Electric Screwdriver Set	Small Electric Precision Screwdriver with 5 Torque Levels, Max 0.75N.m, 500mAh Battery, 50-in-1 Cordless Power Screwdriver Kit for Laptop, Phone & Electronics Repair

**Item 22: SHURE BRAND Podium microphone with BASE**

**Warranty:** Minimum 6 months

**Quantity:** 2

Specification	Description / Features
Shure CVG18DRS-B/C-X Gooseneck Microphone 18 inch With Base and Mute Switch	<p>Electret-condenser gooseneck microphone with integrated desktop base For use in installed sound reinforcement or conferencing Cardioid polar pattern with tailored response for speech while reducing the chance for feedback 18" dual-section gooseneck enables ease of positioning and placement Attached preamplifier, Mute switch, Light-ring indicator Includes integrated 12' cable with XLR termination Plug-and-play connection minimizes setup time Equipped with Comm Shield Technology to filter out unwanted RF interference from portable wireless devices (smartphones, etc.)</p>





### Item 23: Foldable Desktop Microphone Stand

**Quantity:** 3

Specification	Description / Features
Foldable Desktop Microphone Stand with Mic Holder	Tabletop boom microphone stands with microphone holder The legs can be folded, lightweight and portable.

### Item 24: Portable SSD (2TB) – NVME

**Warranty:** minimum 06 months

**Quantity:** 4

Specification	Description / Features
Portable SSD (2TB) _ NVME	2TB, USB 3.2 Gen 2 (10Gb/s) via USB-C connection Up to 1,050 MB/s Up to 1,050 MB/s (for X9 Pro version; standard X9 has read speed specified) 65 x 50 x 10 mm (2.56 x 1.97 x 0.39 in) Approximately 32g (for 1TB model) Shock and vibration resistant; drop proof up to 7.5 feet (2 meters) IP55 water and dust resistance (protection against dust and water jets) Windows, Mac, iPad Pro, Chromebook, Android, Linux, PS4, PS5, and Xbox

### Item 25: Conference System

**Warranty:** Minimum 6 Months

**Quantity:** 1

Specification	Description / Features
Conference System	Speaker: Built-In Hi-Fi Speaker Microphone Array: Built-In 4 Microphone Array Extension Microphone: 2x Wireless Extension Microphone AI-Enabled PTZ Camera with Integrated Microphone & c/w 4x Extension Microphones

### Item 26: Portable Monitor Mount

**Quantity:** 7

Specification	Description / Features
Portable Monitor Stand	Ultra-Lightweight: Just 225g (0.5 lbs). Adjustable Height: Extends up to 39cm for an ergonomic screen height. Compact & Travel-Friendly: Folds down to just 22cm for seamless storage in your bag. Weight limit: Holds portable monitors up to 900g (2 lbs)





### Item 27: Wireless Mic System

**Warranty:** Minimum 6 Months

**Quantity:** 2

Specification	Description / Features
Wireless Receiver	<p>Power Requirements: 12–15 V DC supplied by external power supply Output</p> <p>Impedance: XLR connector: 200 Ω</p> <p>6.35 mm (1/4") connector: 50 Ω</p> <p>Audio Output Level: XLR connector: -27 dBV (into 100 kΩ load)</p> <p>6.35 mm (1/4") connector: -13 dBV (into 100 kΩ load)</p> <p>RF Sensitivity: -105 dBm for 12 dB SINAD, typical</p> <p>Image Rejection: &gt;50 dB, typical</p>
Bodypack Transmitter	<p>Audio Input Level: gain max -16 dBV maximum</p> <p>min (0 dB): +10 dBV maximum</p> <p>Gain Adjustment Range: 26 dB</p> <p>Input Impedance: 1MΩ</p> <p>RF Transmitter Output: 10 mW</p> <p>Power Requirements: 2 LR6 AA batteries</p>
Handheld Transmitter	<p>Audio Input Level: gain 0dB -20 dBV maximum</p> <p>-10dB: -10 dBV maximum</p> <p>Gain Adjustment Range: 10 dB</p> <p>RF Transmitter Output: 10 mW</p>

### Item 28: 2.0 Usb Pendrive 16GB

**Quantity:** 4

Specification	Description / Features
2.0 USB Pendrive 16GB	A USB 2.0 pen drive, officially known as <b>Hi-Speed USB</b> , offers a theoretical maximum signaling rate of <b>480 megabits per second (Mbps)</b> , a significant improvement over its predecessor. In practice, however, typical real-world transfer speeds usually max out around 30-40 megabytes per second (MB/s).

### Item 29: Portable Touch monitor

**Warranty:** Minimum 12 Months

**Quantity:** 5

Specification	Description / Features
Display Size	15.6"
Active Display Area(mm)	344x194
Panel type	In-Plane Switching
Max. Resolution and Refresh Rate	USB-C: 1920x1080@144Hz
Mini HDMI: 1920@1080@144Hz	
Response Time	8ms (G to G)
Contrast Ratio	1200:1 (Native)
Brightness *	250 cd/m <sup>2</sup>





Viewing Angle	170°(H), 170°(V)
Colors	16.7M
Color gamut	45% NTSC
Bits	6Bit+FRC
Input Signal	2 x USB-C
1 x Mini HDMI	
1 x Micro-USB	
Speaker + Audio out	
VESA Wall Mounting	N/A
Speaker	1W x 2
Power Supply (100 - 240 V)	External Adapter
Tilt	0° – 80°
Swivel	N/A
Pivot	N/A

### Item 30: Camera Side bag 3L

Quantity: 2

Specification	Description / Features
Camera Side bag 3L	Black Sling Strap, Handle Zipper Adjustable Dividers (Hook & Loop) Water Resistant (Material) Exterior 12.01 x 7.68 x 4.33" / 30.51 x 19.51 x 11 cm Interior 7.8 x 3.5 x 2.52" / 19.81 x 8.89 x 6.4 cm Weight 0.99 lb / 0.45 kg (Empty)

### Item 31: Windows Tablet

Quantity: 2

**Warranty: Minimum 12 months**

Product Specifications

Specification	Description / Features
Processor	Snapdragon X Plus (10 Core), with LCD display
NPU	Qualcomm Hexagon with 45 TOPS
Graphics	Qualcomm Adreno GPU
Memory and storage	16GB RAM Removable solid-state drive (Gen 4 SSD): 256GB
Display	Touchscreen: 13" PixelSense Flow display20 Resolution: 2880 x 1920 (267 PPI) Aspect ratio: 3:2 Contrast ratio: 1200:1





	<p>Dynamic refresh rate: up to 120Hz</p> <p>Color profile: sRGB and Vivid</p> <p>Individually color-calibrated display</p> <p>Adaptive color</p> <p>Adaptive contrast</p> <p>Auto color management</p> <p>Touch: 10-point multi-touch</p> <p>Dolby Vision IQ™21</p> <p>Corning® Gorilla® Glass 5</p> <p>Brightness: SDR: 600 nits maximum (typical)</p> <p>HDRvi: 600 nits peak luminance</p>
Size and weight	<p>Length: 11.3 inch (287 mm)</p> <p>Width: 8.2 inch (209 mm)</p> <p>Height: 0.37 inch (9.3 mm)</p> <p>Weight: 1.97 lbs (895 g)</p>
Security	<p>Enhanced security with Microsoft Pluton TPM 2.0</p> <p>Windows 11 Secured-core PC</p> <p>Windows Hello face authentication with Enhanced Sign-in security</p> <p>Microsoft Defender – for enhanced identity and privacy protection*</p>
Cameras	<p>Quad HD front-facing camera</p> <p>1440p Quad HD camera with ultrawide field of view</p> <p>10MP Ultra HD rear-facing camera</p> <p>Windows Hello face authentication camera</p>
Audio	<p>Dual Studio Mics with enhanced voice focus</p> <p>2W stereo speakers with Dolby Atmos</p> <p>Support for Bluetooth LE Audio</p>
Ports and charging	<p>2 X USB-C® / USB4 ports with support for:</p> <p>Charging</p> <p>Data transfer</p> <p>DisplayPort 1.4a</p> <p>Thunderbolt 4 Dock and other accessories</p> <p>Supports fast charging</p> <p>Keyboard port</p>
Network and connectivity	<p>Wi-Fi 7</p> <p>Bluetooth® Core 5.4 technology</p>
Operating System	Windows 11
Exterior	Color: Sapphire
Kickstand	Kickstand with 165 degrees full friction hinge
Sensors	<p>Ambient color sensor</p> <p>Accelerometer</p> <p>Gyroscope</p> <p>Magnetometer</p>





**Item 32: Wi-Fi 6 APN**

**Quantity:** 4

**Warranty:** Minimum 06 months

## **Authorization Letter: Required**

Specification	Description / Features
Wi-Fi APN	Dimensions Ø220 x 48.1 mm Environment Indoor/Outdoor 2.4 GHz Radio Rate 800 Mbps 5 GHz Radio Rate 1733 Mbps PoE Mode 802.3at PoE+ Ports (2) 10/100/1000 Ethernet Wi-Fi Users 500+ Users Wi-Fi 6

### Item 33: Document Scanner

**Quantity:** 2

**Warranty:** Minimum 06 months

Specification	Description / Features
Connectivity Technology	Wi-Fi
Product Dimensions	11.6"D x 11.6"W x 6.9"H
Resolution	300
Item Weight	8.1 Pounds
Wattage	11 watts
Color Depth	8 bpp
Standard Sheet Capacity	50

### Item 34: Wireless Miracast Device

**Quantity: 7**

**Warranty:** Minimum 03 months

Specification	Description / Features
Operating system	Windows 10 and higher macOS 11 and higher Android v11 and higher iOS 14 and higher
System requirements	For smooth experience with Microsoft Teams or Zoom Minimum: Intel i3 dual-core processor or AMD Ryzen 7 / 8GB RAM / OS: Windows 10 latest build or Mac OS Mojave latest build Recommended: Intel i5 4-core processor or AMD Ryzen 9 / 8GB RAM / OS: Windows 11 latest build or Mac OS latest build
Video outputs	4K UHD (3840*2160) 30Hz. HDMI™ 1.4b or USB-C DisplayPort 1.2 (only Gen2)
Audio output	USB, HDMI
USB	1 X USB-A, 1 X USB-C
Buttons	2



App	Desktop & Mobile
Native protocols	Airplay, Google Cast, Miracast
Maximum sources simultaneously on screen	2
Noise Level	Max. 25dBA @ 0-30°C Max. 30dBA @ 30-40°C
Authentication protocol	WPA2-PSK in standalone mode WPA2-PSK or IEEE 802.1X using the Button in network integration mode
Wireless transmission protocol	IEEE 802.11 a/g/n/ac and IEEE 802.15.1
Reach	Max. 30m (100 ft) between Button and Base Unit Frequency band 2.4 GHZ and 5 GHz (DFS)
Frequency band	1x Ethernet LAN 1Gbit 1x USB-C 2.0 (front); 1x USB-A 2.0 (front) -only Gen2: 1x USB-C 3.0 (front); 1x USB-A 3.0 (front)
Connections	1x Ethernet LAN 1Gbit 1x USB-C 2.0 (front); 1x USB-A 2.0 (front) -only Gen2: 1x USB-C 3.0 (front); 1x USB-A 3.0 (front)
Temperature range	Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F)
Humidity	Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing
Anti-theft system	Kensington lock
Certifications	FCC/CE
Touch screen support & Interactivity	Yes
Wireless conferencing	via App or Button
Local view	Yes
Network connection	LAN & WiFi

### Item 35: Portable Conference Camera Pillar (all in one)

Quantity: 4

Warranty: Minimum 06 months

Specification	Description / Features
Portable Conference Camera Pillar (all in one)	<p>Design: The device features a sleek, all-in-one design that is easy to use, manage, and portable, allowing for quick meeting setups.</p> <p>Video: It provides 1080p HD video imaging with a 120° wide-angle viewing without distortion, ensuring everyone in the room is visible.</p> <p>Audio: The All-in-One Pillar X12 includes an integrated speaker and four microphones to ensure clear audio pick-up and playback.</p> <p>Functionality: It supports smart features like auto-framing and speaker focusing to enhance the conferencing experience.</p> <p>Compatibility: The device is compatible with popular video conferencing software such as Zoom, Webex, Tencent Meeting, WeChat, and Ding Talk.</p> <p>Connectivity: The camera component connects via USB 2.0.</p>





**Item 36 :IP bullet Camera (Outdoor Specialized))**

**Quantity:** 80

**Warranty:** Minimum 06 months

**Authorization Letter:** Required

Specification	Description / Features
IP Bullet Camera (Outdoor Specialized)	<p>F1.0 lens and sensitive sensors capture more light for full-color video in near darkness.</p> <p>Warm LED lights are used to illuminate scenes in low light, enabling vivid color imaging.</p> <p>AI-powered analytics can distinguish between humans and vehicles, reducing false alarms.</p> <p>High-quality construction and weather resistance ensure durability.</p> <p>Some advanced models offer features like panoramic views, 4MP resolution, and smart dual-light technology.</p> <p>Should Support Hikvision NVR</p>

**Item 37: Dome Camera**

**Quantity:** 70

**Warranty:** Minimum 06 months

**Authorization Letter:** Required

Specification	Description / Features
4MP Fixed IR Dome Network Camera	<p>High quality image with 4MP, 1/3" CMOS sensor</p> <p>4MP (2560 × 1440) @25/20 fps; 3MP (2304 × 1296) @25/20 fps; 2MP (1920 × 1080) @30/25 fps</p> <p>Ultra 265, H.265, H.264</p> <p>Smart IR, up to 30 m (98 ft) IR distance</p> <p>Day/night functionality</p> <p>2D/3D DNR (Digital Noise Reduction)</p> <p>IP67 protection</p> <p>IK10 vandal resistant</p> <p>DC12 V or PoE (IEEE 802.3af) power supply</p> <p>Should Support Hikvision NVRs</p>

**Item 38: Junction Box (For IP Bullet Camera)**

**Quantity:** 100

Specification	Description / Features



Junction Box (For IP Bullet Camera)	<p>Material: Aluminum alloy or tough, UV-resistant plastic.</p> <p>Weather Rating: IP66 for outdoor use.</p> <p>Cable Management: Features multiple concealed ports for wire entry.</p> <p>Mounting: Pre-drilled holes for compatibility with most bullet camera bases.</p> <p>Dimensions: Varies; check the specific product for measurements.</p> <p>Should support Bullet camera's base</p>
-------------------------------------	--

**Item 39: Junction Box (For IP dome camera)**

Quantity: 100

Specification	Description / Features
Junction Box (For IP dome camera)	<p>Material: Aluminum alloy or tough, UV-resistant plastic.</p> <p>Weather Rating: IP66 for outdoor use.</p> <p>Cable Management: Features multiple concealed ports for wire entry.</p> <p>Mounting: Pre-drilled holes for compatibility with most bullet camera bases.</p> <p>Dimensions: Varies; check the specific product for measurements.</p> <p>Should support Bullet camera's base</p>

**Item 40: Surveillance Hard Disk (8TB)**

Quantity: 8

Warranty: Minimum 06 months

Specification	Description / Features
Surveillance Hard Disk (8TB)	<p>24/7 Reliability: Built for constant, high-volume video recording, unlike standard desktop drives.</p> <p>Optimized Firmware: Manages continuous streams to prevent dropped frames.</p> <p>Anti-Vibration (RV) Sensors: For stable performance in multi-drive systems (on high-end models).</p> <p>Low Power: Designed for cooler operation and reliability in always-on environments.</p>

**Item 41: 1 HDD NVR**

Quantity: 5

Warranty: Minimum 06 months

Authorization Letter: Required

Specification	Description / Features
1 HDD NVR	<ul style="list-style-type: none"> <li>Support Ultra265/H.265/H.264 video formats</li> <li>16-channel or more input</li> <li>Third-party IP cameras supported with ONVIF conformance: Profile S, Profile G, Profile T</li> <li>HDMI and VGA simultaneous output</li> <li>Up to 8 Megapixels resolution recording</li> </ul>





