





REVISED
28/02/2025

Information Sheet for Dewatering Equipment's

QTY	Items	Specification
1500 m	Dewatering Pipe Hose	<p>Material: PVC Feature: Adjustable, Anti-Abrasion, Anti-Corrosion, Flexible, Soft Diameter 4 inch Quality: First-Class and Durable Working Pressure: minimum 6 BAR</p> 
5	Submersible Pump	<p>Outlet: 1.5-inch Material: Cast Iron/Stainless steel Structure: Single-stage Pump Power: Electric Start Up: Electric Pump / without floating switch Warranty: 1 year Pressure: 3 - 4 bar Flow rate: not less than 25 m³/h (Image for reference only)</p>



REVISED
28/02/2025

		
1	Sludge Pump	<p>Output size: 6 inches Anti-corrosive and rust proof Usage: Water and sewage Fuel: Diesel Application: commercial Buildings, District Energy, Industrial Boilers, Industrial Utilities, Irrigation and Agriculture, Mining industry, Washing and Cleaning, Wastewater Transport and Flood Control, wastewater treatment, Water Distribution, Water Treatment Solutions Structure: Single stage pump Material: Cast Iron/Stainless steel Warranty: 2 years Flow rate: Not less than 330 m3/h All necessary fittings for suction should be included Should be easy to carry, with wheels. Refer to diagram (for reference only)</p>



REVISED
28/02/2025

300 m	Spiral Pipe	<p>Diameter: 6 inches Working pressure: Should be able to withstand sludge pump pressure</p>
250m	Canvas (Sathari) Hose	<p>Diameter: 1.5 inches Working pressure: Should be able to withstand submersible pump pressure</p>
50 pcs	Bolt Head Hose Clamp	<p>Size: 4 inches Material: Stainless steel</p>



REVISED
28/02/2025

			
50 pcs	Bolt Head Hose Clamp	Size: 3 inches Material: Stainless steel	