



۵۴

۞ تَبٰرَكَ الَّذِي يَخْلُقُ مَا يَشَاءُ ۚ وَهُوَ يُعَلِّمُ مَا يَشَاءُ ۚ وَهُوَ الْعَزِيزُ الرَّحِيمُ ۝
 ۞ وَلَقَدْ عَلَّمْنَا الْبَشَرَ كُلَّ شَيْءٍ مَّا هُوَ حَافِظٌ لِّمَا بَيْنَ يَدَيْهِ ۚ وَهُوَ الْعَزِيزُ الرَّحِيمُ ۝
 ۞ وَلَقَدْ عَلَّمْنَا الْبَشَرَ كُلَّ شَيْءٍ مَّا هُوَ حَافِظٌ لِّمَا بَيْنَ يَدَيْهِ ۚ وَهُوَ الْعَزِيزُ الرَّحِيمُ ۝
 ۞ وَلَقَدْ عَلَّمْنَا الْبَشَرَ كُلَّ شَيْءٍ مَّا هُوَ حَافِظٌ لِّمَا بَيْنَ يَدَيْهِ ۚ وَهُوَ الْعَزِيزُ الرَّحِيمُ ۝
 ۞ وَلَقَدْ عَلَّمْنَا الْبَشَرَ كُلَّ شَيْءٍ مَّا هُوَ حَافِظٌ لِّمَا بَيْنَ يَدَيْهِ ۚ وَهُوَ الْعَزِيزُ الرَّحِيمُ ۝

**Supply of Furniture and IT Equipment for
Selected Buildings under the Management of
Kulhudhuffushi City Council**

PC-266/2026/W-34

٥٠٥٤٠٠
٥٠٥٤٠٠

(IUL)266-PR/266/2026/192

درجہ اولیٰ

28 ۛۛۛۛۛۛۛ 2026

[illegible]

وَحُورٌ ۱

مَنْ يَتَّقِ اللَّهَ يَجْعَلْ لَهُ مَخْرَجًا

2026 28 ستمبر کو

[illegible]

1

2

1	2
1.1	28
8.1	10:30
9.2	8
9.2	10:30
13.1	12
17.1	10:30
19.1	10:30
22.1	6
30.1	500.00
32.1	2.5%



سورة صافات - 2 -

(۱) رَسْرَسْ دَ جَ دَ دَ دَ دَ دَ دَ دَ دَ دَ دَ دَ دَ دَ دَ دَ دَ دَ D

- [illegible]

[illegible][illegible][illegible][illegible]

3.3.5 سَوْنَرَنَ نَسْرَنَسَرَنَ، جَوَنَ مَجْعَ نَسْرَنَسَرَنَ نَسْرَنَسَرَنَ مَجْعَ
مَسْرَنَسَرَنَ سَوْنَرَنَ، جَسْرَنَسَرَنَ نَسْرَنَسَرَنَ مَسْرَنَسَرَنَ مَسْرَنَسَرَنَ.

[illegible][illegible][illegible]

6.2. د ژانرې 6.1 د اوسنۍ وروستۍ لړزې په پرتله کې،
د وروستۍ وروستۍ 19.01 وسه ژانرې (س) د "لاندې برخې" سره
"لاندې برخې" ته د وروستۍ وروستۍ سره سمون ورکوي.
په دې توګه.

(A) **ආර්ථික ක්ෂේත්‍රයේ**

7. **ආර්ථික ක්ෂේත්‍රයේ** 7.1 **ආර්ථික ක්ෂේත්‍රයේ** 7.1.1 **ආර්ථික ක්ෂේත්‍රයේ** 7.1.2 **ආර්ථික ක්ෂේත්‍රයේ** 7.1.3 **ආර්ථික ක්ෂේත්‍රයේ** 7.1.4 **ආර්ථික ක්ෂේත්‍රයේ** 7.1.5 **ආර්ථික ක්ෂේත්‍රයේ** 7.1.6

7.1.1 **ආර්ථික ක්ෂේත්‍රයේ** (1-වන කොටස)

7.1.2 **ආර්ථික ක්ෂේත්‍රයේ** (2-වන කොටස)

7.1.3 **ආර්ථික ක්ෂේත්‍රයේ** (3-වන කොටස)

7.1.4 **ආර්ථික ක්ෂේත්‍රයේ** (4-වන කොටස)

7.1.5 **ආර්ථික ක්ෂේත්‍රයේ** (5 - වන කොටස)

7.1.6 **ආර්ථික ක්ෂේත්‍රයේ** (6-වන කොටස)

8. **ආර්ථික ක්ෂේත්‍රයේ** 8.1 **ආර්ථික ක්ෂේත්‍රයේ** 8.2 **ආර්ථික ක්ෂේත්‍රයේ** 9.1 **ආර්ථික ක්ෂේත්‍රයේ** 9.2 **ආර්ථික ක්ෂේත්‍රයේ** 9.3 **ආර්ථික ක්ෂේත්‍රයේ** 10.1 **ආර්ථික ක්ෂේත්‍රයේ** 10.2

8.2 **ආර්ථික ක්ෂේත්‍රයේ** 9.1 **ආර්ථික ක්ෂේත්‍රයේ** 9.2 **ආර්ථික ක්ෂේත්‍රයේ** 9.3 **ආර්ථික ක්ෂේත්‍රයේ** 10.1 **ආර්ථික ක්ෂේත්‍රයේ** 10.2

9. **ආර්ථික ක්ෂේත්‍රයේ** 9.1 **ආර්ථික ක්ෂේත්‍රයේ** 9.2 **ආර්ථික ක්ෂේත්‍රයේ** 9.3 **ආර්ථික ක්ෂේත්‍රයේ** 10.1 **ආර්ථික ක්ෂේත්‍රයේ** 10.2

9.2 **ආර්ථික ක්ෂේත්‍රයේ** 9.3 **ආර්ථික ක්ෂේත්‍රයේ** 10.1 **ආර්ථික ක්ෂේත්‍රයේ** 10.2

9.3 **ආර්ථික ක්ෂේත්‍රයේ** 10.1 **ආර්ථික ක්ෂේත්‍රයේ** 10.2

10. **ආර්ථික ක්ෂේත්‍රයේ** 10.1 **ආර්ථික ක්ෂේත්‍රයේ** 10.2

10.1 **ආර්ථික ක්ෂේත්‍රයේ** 10.2

[illegible]

24.7. حَ دَرْتَرُ (س) زِ ا هَوَسَنَسَرَجِرُو رَحَمُونُ فَعْمُو مَخَدَرُ سَرُمُو سَرُدُ،

[illegible]

24.8. (ع) دَورِ تَرْتِی (س) زَبِّ هَوَسْ سَهْرُ قِرْقُو رَحْمَتِ نَعْمُو حَوْذَرِ شَرْمِ سَدْرِ

اِسْرَافُ دَمِيسَرِ عَسِرِ نَحْرِوْ تَارُو حِرَو قَزَعُو هَوَسَرِ رَوَوَنَدِ مَسَرِ
سِرِنْدَرِ رَوَوَنَدِ اَرْفُو.

24.9. (ع) د دږترس (ه) زړ هږسرانر نړو شووړن نړو هږدږ سرور،

اِسْمُكَ دَمِيسُ مَسْرُومُ لَمْعُو فَرْوُ نَمْعُو هُوَسُ رَوُو مَسْرُ
 مَسْرُ دَمِيسُ مَسْرُومُ

25. $\text{مُحَمَّدٌ رَجُلٌ مِّنْ أَهْلِ الْبَيْتِ}$ 25.1 $\text{مُحَمَّدٌ رَجُلٌ مِّنْ أَهْلِ الْبَيْتِ}$ $\text{مُحَمَّدٌ رَجُلٌ مِّنْ أَهْلِ الْبَيْتِ}$

$\frac{6}{\sqrt{e}} \approx 0.7$, $\frac{\pi}{\sqrt{e}} \approx 1.1$, $\frac{\ln e}{\sqrt{e}} = 1$

[illegible]

حَافِظِي سِرِّي. سِرِّهِ;

25.3. (ر) هَوَسُوْخَرَا، خُخَرَا، سَرُوْ، وَهَرَا، سَرَدَ، رَ وَهَرَا

مَرْجِعُ كُلِّ شَيْءٍ عِندَ رَبِّهِ ۖ فَكَيْفَ يُعْذِرُ الْمُكَذِّبِينَ ۖ

25.4. (س) د خوږ ترخه (ـ) رڼه (ر) زړه هوسنه سترگو وروڼه پورې سره سمون

سَمْعًا بَرًّا قَرِيْبًا ۚ وَخُذْ زِيَارَةَ الْهَيْكَلِ الَّذِي بَنَىٰ لَكُمُ الْمَلِكُ دَاوُدُ ۚ وَلَا تَجْزَلْ ۚ إِنَّكُم بِأَعْيُنِنَا ۚ وَخُذْ الْحَقَّ ۚ إِنَّكُم مُّخْرَجُونَ ۚ

25.5. (1) $\vec{u} = \vec{u}_1 + \vec{u}_2 + \vec{u}_3$, $\vec{u}_1 = \vec{u}_2 = \vec{u}_3 = \vec{u}$

اِنَّكُمْ لَعِندَ رَبِّكُمْ
۱ وَسَرُورٌ اِنَّكُمْ لَمَعْمُورٌ

[illegible]

25.6 (2) $\frac{1}{2} \frac{d}{dt} \left(\frac{1}{2} m v^2 \right) = \frac{1}{2} m v \frac{dv}{dt} = \frac{1}{2} m v \frac{dv}{dt} = \frac{1}{2} m v \frac{dv}{dt}$

وَمِنْ ثَمَرَاتِهِ سِدْرٌ، وَشَجَرٌ رَاسِمْ رَاسِمْ جَعَلُوا سِدْرٌ 1

وَسَرُّ خُورٍ ا وَنَزِيرٌ مَجْجُوٌّ مَخْرُوجٌ مَدْرُسٌ مُرَوِّعٌ

25.7 (3) 25.7

25.8 25.8

25.9 25.9

25.10 25.10

25.11 25.11

25.12 25.12

26 26.1 26.1

26.2 26.2

26.3 26.3

26.4 26.4

26.5 26.5

27 27.1 27.1

27 27.1 27.1

[illegible]

3 - 38

38.1 38.2 38.3 38.4 38.5 38.6 38.7

- 38.1 "38.2 38.3 38.4 38.5 38.6 38.7
- 38.2 "38.3 38.4 38.5 38.6 38.7
- 38.3 "38.4 38.5 38.6 38.7
- 38.4 "38.5 38.6 38.7
- 38.5 "38.6 38.7
- 38.6 "38.7
- 38.7 "38.8

38.1 38.2 38.3 38.4 38.5 38.6 38.7

- 39.1 39.2 39.3 39.4 39.5 39.6 39.7
- 39.2 "39.3 39.4 39.5 39.6 39.7
- 39.3 "39.4 39.5 39.6 39.7
- 39.4 "39.5 39.6 39.7
- 39.5 "39.6 39.7
- 39.6 "39.7
- 39.7 "39.8

39.1 39.2 39.3 39.4 39.5 39.6 39.7

42.3. $2,500,000/-$ 2,500,000/- 2,500,000/- 2,500,000/- 2,500,000/-
0.005 0.005 0.005 0.005 0.005
CP*0.005*LD = CP*0.005*LD = CP*0.005*LD = CP*0.005*LD = CP*0.005*LD =

CP*0.005*LD =

CP (LD) 0.005*LD =

LD (LD) 0.005*LD =

43.1. 43.1. 43.1. 43.1. 43.1.
43.2. 43.2. 43.2. 43.2. 43.2.
43.3. 43.3. 43.3. 43.3. 43.3.
43.4. 43.4. 43.4. 43.4. 43.4.

43.2. 43.2. 43.2. 43.2. 43.2.
43.3. 43.3. 43.3. 43.3. 43.3.
43.4. 43.4. 43.4. 43.4. 43.4.

43.3. 43.3. 43.3. 43.3. 43.3.
43.4. 43.4. 43.4. 43.4. 43.4.

43.4. 43.4. 43.4. 43.4. 43.4.
44.1. 44.1. 44.1. 44.1. 44.1.
44.2. 44.2. 44.2. 44.2. 44.2.

44.1. 44.1. 44.1. 44.1. 44.1.
44.2. 44.2. 44.2. 44.2. 44.2.

44.2. 44.2. 44.2. 44.2. 44.2.

4 - 4

4

1 - 1

4

#	4	4
4		
1.	4	4
2.	4	4
3.	4	4
4.	4	4
5.	4	4
6.	4	4
7.	4	4
8.	4	4
4		
9.	4	4
10.	4	4
4		
11.	4	4
12.	4	4
13.	4	4
14.	4	4
4		
15.	4	4
16.	4	4

2 - 2

2

1. 2	
1.1	
1.2	
1.3	
1.4	
1.5	
2. 2	
2.1	
2.2	(IUL)266-PR/266/2026/192
3. 2	
3.1	
3.2	
4. 2	
4.1	
4.2	
4.3	
5. 2	

3 - مع مَرَوُوعُ

تَرْجُومُو 5 (تَرْجُومُو) تَرْجُومُو تَرْجُومُو تَرْجُومُو تَرْجُومُو تَرْجُومُو تَرْجُومُو

[illegible]

5 (ދިވެހިސަރުކާރުގެ ގެޒެޓް)

Form of Bid Security (Bank Guarantee)

WHEREAS,[name of Bidder] (hereinafter called “the Bidder”) [company registration number] has submitted his Bid for the Project no.....issued by the Secretariat of Kulhudhuffushi City Council onfor construction of[name of Contract] (hereinafter called “the Bid”) under Invitation of bidders No. [Announcement Number]

KNOW ALL PEOPLE by these presents that We [name of Bank] of [name of country] having our registered office at (hereinafter called “the Bank”) are bound unto[name of Purchaser] (hereinafter called “the Purchaser”) in the sum of *..... for which payment well and truly to be made to the said Purchaser, the Bank binds itself, its successors, and assigns by these presents.

SEALED with the Common Seal of the said Bank thisday of20.....

THE CONDITIONS of this obligation are:

- (1) If, after Bid opening, the Bidder withdraws his Bid during the period of Bid validity specified in the Form of Bid;
or
- (2) If the Bidder having been notified of the acceptance of his Bid by the Purchaser during the period of Bid validity:
 - (a) fails or refuses to execute the Form of Agreement in accordance with the Instructions to Bidders, if required; or
 - (b) fails or refuses to furnish the Performance Security, in accordance with the Instruction to Bidders; or
 - (c) does not accept the correction of the Bid Price pursuant to Clause 27,

* The Bidder should insert the amount of the Guarantee in words and figures denominated in Maldivian Rufiyaa. This figure should be the same as shown in Clause 28.1 of the Instructions to Bidders.

we undertake to pay to the Purchaser up to the above amount upon receipt of his first written demand, without the Purchaser's having to substantiate his demand, provided that in his demand the Purchaser will note that the amount claimed by him is due to him owing to the occurrence of one or any of the three conditions, specifying the occurred condition or conditions.

This Guarantee will remain in force up to and including the date days after the deadline for submission of bids as such deadline is stated in the Instructions to Bidders or as it may be extended by the Purchaser, notice of which extension(s) to the Bank is hereby waived. Any demand in respect of this Guarantee should reach the Bank not later than the above date.

DATE..... SIGNATURE OF THE BANK

WITNESS SEAL

[signature, name, and address]

5 - ٲٲٲٲٲٲ

ٲٲٲٲٲٲ ٲٲٲٲ

No.	Description	Quantity	Rate	Total
1.	Foldable Meeting/Conference Table	62		
2.	Foldable Chair	160		
3.	Foldable Table With Cloth Cover (Cloths 24 PCS)	12		
4.	Cocktail Table With Covering Cloths (Covering Cloths 16 PCS)	8		
5.	Dustbin	4		
6.	Interactive Flat Panel Displays (IFPs) with Stand	1		
7.	Card Holder Sofa	10		
8.	120cm Long Table with Wood Veneer	7		
9.	60cm Wooden Leather Square Table	10		
10.	Single Chair	15		
11.	Podium	1		
12.	Ergonomic Chair	18		
13.	Bean Bag	5		
14.	Velvet Storage Stool	10		
15.	Training Chair with Table Board	50		
16.	Powered Loudspeaker	2		
17.	Channel Digital Anti-Feedback Processor	2		
18.	HDMI Cable (High Speed)	10		
19.	IEC C13 'Kettle' Power Cable Lead with UK Pin Plug	10		
20.	USB-C to HDMI Multiport Adapter	10		
21.	Softbox	2		
22.	Bi Color LED Video Light	2		
23.	Air Cushioned Light Stand	2		
24.	Split ND Filter Set for DJI Mavic 4 Pro (2–3 Stops)	1		
25.	Cooling Fan for Sony Camera	2		
26.	Micro-HDMI to HDMI Cable	1		
27.	COB Light	1		
28.	Camera Strap	2		
29.	SD Card – 128GB	3		
30.	SD Card – 265GB	2		
31.	Closed Back Audio Monitor	2		
32.	Lens Cap	1		
33.	SD Card Reader	3		

34.	Charger for Godox V860III-S (VC26 Battery Charger)	1		
35.	Clip-on Wireless Microphone	1		
			Sub Total	
			GST 8%	
			Net Total	

6 -

1.

1.1

1.2

1.3

1.4

1.5

1.6


Item Name	Quantity	Specification	Artwork
Foldable Meeting/conference Table See full pictures in Annex 1	62	- Base/Bracket: 3.0mm-thick magnesium - Column: 2mm-thick aluminum - Beam: 50 X 25 X 1.5mm cold-rolled steel, length adjustable - Metal colors: white - Glide: PP· Optional lockable 2.5inch PU castors - Wood top foldable· Stackable for space saving - With Modesty panel, length adjustable	 

		➤ Overall length: 1200mm ➤ Overall width: 600mm ➤ Overall height: 750mm	
Foldable chair See full pictures in Annex 2	160	Crafted from highly durable magnesium and fabric for a comfortable seat, and magnesium alloy legs for the toughest of lives. Quickly foldable and side stacked. With Castor-wheels. <u>Features</u> ▪ Light-weight and Durable Die cast Aluminium Chair Frame in Stackable design for neater environment ▪ Moulded Foam Seat with Customizable Fabric Colors ▪ Hard-wearing Nylon Castor Wheels allows Ease of Manoeuvring while Protecting Flooring <u>Dimensions in mm</u> Overall width: 595mm Overall Height: 870mm Floor to seat height: 465mm Castor Wheel: 3.5 inch <u>Material</u> ▪ Die Cast Aluminium Chair Frame ▪ Fabric Foam Cushion Seat ▪ Nylon Wheel Castor Color need to be aproved	 

Foldable Table With Cloth Cover, Cloths (24 PCS) See full pictures in Annex 3	12	▪ NBH – Folding Table ▪ Portable ▪ Brand: NBH ▪ Model: HTR150F ▪ Color: White/Grey ▪ Material: Plastic + Metal Legs ▪ Features: ▪ Seats 6 to 8 people. ▪ Easy to fold and carry with handle. ▪ Suitable for indoor or outdoor settings. ▪ Space-Saving: Folds flat for easy storage. ▪ Durable Build: Sturdy plastic top and metal legs ensure long-lasting use. ▪ Dimension: ▪ Width x Depth x Height ▪ Millimeter (mm): ▪ Dia· 1520 x H 730mm ▪ Inch ("): ▪ Dia· 59.8” x H 28.7” ▪ Feet (') Inch ("): ▪ Dia· 5’ x H 2’5” ▪ Folded Dimension: W 1520 x D 760 X H 90mm (W 59.8” x D 29.9” x H 3.5”)	
Coctail Table With Covering Cloths (Covering Cloths 16 PCS)	8	▪ MNI - Dining Table ▪ Brand: MNI ▪ Model: DT510 ▪ Color: White ▪ Shape: Round ▪ Material: Plastic ▪ Dimension	

See full pictures in Annex 4		▪ Diameter x Height ▪ Millimeter (mm): ▪ Dia· 700 x H 1050mm ▪ Inch ("): ▪ Dia· 27.6” x H 41.3” ▪ Feet (') Inch ("): ▪ Dia· 2'4" x H 3'5”																			
Dutbin See full pictures in Annex 5	4	Height 600mm Stainless Steel Foot Pedal Round shape 27L																			
Interactive Flat Panel Displays (IFPs) with Stand See full Information in Annex 6	1	<table><tr><th>Component</th><th>Technical Parameter</th><th>Minimum Requirement Specifications</th></tr><tr><td rowspan="4">Display & Visuals</td><td>Screen Type</td><td>Direct-lit LED Backlight with Anti-Glare/Anti-Fingerprint tempered safety glass.</td></tr><tr><td>Display Size</td><td>98-inch diagonal minimum.</td></tr><tr><td>Native Resolution</td><td>3840 x 2160 (4K UHD) at a minimum refresh rate of 60Hz.</td></tr><tr><td>Aspect Ratio</td><td>16:9 widescreen format.</td></tr><tr><td></td><td>Viewing Angle</td><td>178° horizontal and vertical minimum.</td></tr><tr><td></td><td>Display Colors</td><td>1.07 Billion colors (10-bit) with automated ambient light brightness adjustments.</td></tr></table>	Component	Technical Parameter	Minimum Requirement Specifications	Display & Visuals	Screen Type	Direct-lit LED Backlight with Anti-Glare/Anti-Fingerprint tempered safety glass.	Display Size	98-inch diagonal minimum.	Native Resolution	3840 x 2160 (4K UHD) at a minimum refresh rate of 60Hz.	Aspect Ratio	16:9 widescreen format.		Viewing Angle	178° horizontal and vertical minimum.		Display Colors	1.07 Billion colors (10-bit) with automated ambient light brightness adjustments.	
Component	Technical Parameter	Minimum Requirement Specifications																			
Display & Visuals	Screen Type	Direct-lit LED Backlight with Anti-Glare/Anti-Fingerprint tempered safety glass.																			
	Display Size	98-inch diagonal minimum.																			
	Native Resolution	3840 x 2160 (4K UHD) at a minimum refresh rate of 60Hz.																			
	Aspect Ratio	16:9 widescreen format.																			
	Viewing Angle	178° horizontal and vertical minimum.																			
	Display Colors	1.07 Billion colors (10-bit) with automated ambient light brightness adjustments.																			
Card Holder Sofa 10 PCS Annex 7	10	Overall length: 1200mm Overall width: 600mm Overall height: 1050mm On seat 450mm																			
120cm Long Table with Wood veneer	7	Overall length: 1200mm Overall width: 600mm Overall height: 750mm																			

Annex 7			
60cm Wooden Leather Square Table Annex 7	10	Overall length: 600mm Overall width: 600mm Overall height: 750mm	
Single Chair Annex 7	15	Overall length: 450mm Overall width: 520mm Overall height: 800mm and 450mm	
Podium	1	Overall height: 1140mm Magnetic removable plate with council logo and name	 

Ergonomic chair Annex 8	18	Ergonomic chair Back frame PP+ fiber, head pillow can be up and down the belt hanger Single frame cushion + imported special network 3D lifting handrail Stage 3 locking multi-functional chassis 350MM aluminum fit +60MM all-black PU wheel	 
Bean Bag	5	Color: Royal blue - Cream - Dark Orange Dimentions: 900mm*1100mm Faux linen or other fabric	 90*110CM
velvet storage stool	10	Same as stool in Munus Hub	
Training Chair with Table Board	50	Feature: Material: stand: metal ;armrest: PP; back: mesh felt;Cushion: high density sponge;writing pad: ABS Must include: writing pad and wheels	 

--	--	--	--

Powered Loudspeaker	2	Item Type: 2 x 10" Powered Loudspeaker (Enhanced, Monitor-Capable) Driver Configuration: 10" woofer + 1" compression driver Power Output: 1400W Class-D amplifier Max SPL: 127 dB peak Frequency Response: 52 Hz – 23 kHz (-10 dB) DSP Voicing Modes: Music, Live, Club, Monitor + Indoor/Outdoor settings Monitor Features: Dedicated Monitor voicing mode, built-in monitor wedge angle for floor monitor use Feedback Control: Built-in Feedback Eliminator Channel Features: Music Ducking (auto-reduces Ch-2 when Ch-1 receives signal) Inputs / Outputs: Ch-1: XLR/TRS (mic or line); Ch-2: XLR/TRS line + stereo 1/8" aux; Thru output Wireless Connectivity: Bluetooth playback & control, app-based speaker linking	
----------------------------	---	--	---

		App Support: Companion app for EQ, voicing modes, and channel level control Mounting: Standard pole mount Dimensions: 22.4" x 13.0" x 12.8" (569 x 330 x 325 mm) Weight: 25.6 lb / 11.6 kg (per unit)	
Channel Digital Anti-Feedback Processor	2	Item Type: 2 x 2-Channel Digital Anti-Feedback Processor Channels: 2 Inputs/Outputs: XLR & Jack input and output per channel Operating Modes: Fixed mode (storable filters/presets), Live mode (real-time analysis and editing) Filter Precision: Extremely narrow notch filters, up to 1/80 of an octave Programmable Filters: 24 per channel Indicators: LED chain for all 24 filters per channel, LCD display Connectivity: USB port (firmware updates) Power: Internal power supply Format: 19" / 1U rack unit	

HDMI Cable (High Speed)	10	Item Type: HDMI Cable (High Speed) Length: 15ft / 4.5m Connector Type: HDMI Type A to HDMI Type A HDMI Version: HDMI 2.1 Bandwidth: 48Gbps Resolution Support: Up to 4K@60Hz (backward compatible with 2K, 1080p, 720p) Compatible Devices: MacBook, iMac, Mac Mini, Apple TV, Windows laptops & desktops, Microsoft Surface, monitors, TVs, projectors, and any standard HDMI- enabled device Audio Support: ARC/eARC, multi-channel digital audio Materials: Braided nylon jacket, gold-plated connectors Colour: Black	
IEC C13 'Kettle' Power Cable Lead with UK Pin Plug	10	Item Type: IEC C13 'Kettle' Power Cable Lead with UK Pin Plug Connector Type: C13 (IEC) to UK 3-Pin Plug Length: 10m Fuse Rating: 13A	

		Max Power Capacity: Up to ~2990W at 230V (within 13A fuse limit) — suitable for most amplifier/subwoofer power draw Compatible Devices: Computers, Monitors, Printers, and other electronics with a C13 inlet Safety Features: Moulded strain relief, safety standard compliant Construction: Premium materials for durability and reliable power transfer	
USB-C to HDMI Multiport Adapter	10	Item Type: USB-C to HDMI Multiport Adapter Colour: Gray Ports / Interface: HDMI 2.1, USB-C (PD), USB 3.0, USB 2.0 Compatible Devices: Laptops, Tablets, Smartphones with USB-C (Thunderbolt 3/4 compatible) — MacBook Pro/Air, iPad Pro, Chromebook, Surface Book, Galaxy S21/S20/S10, .etc Charging (Power Delivery): 27W max via USB-C	

		USB Data Transfer Speed: 10 Gbps (USB 3.0 / 3.1 Gen 1) Video Output: 4K (backward compatible with 2K, 1080p, 720p) Materials: Aluminum alloy Dimensions: 2.3" x 2.1" x 0.4" (60 x 55 x 10 mm) Cable Length: 130mm / "0.5 Weight: 0.04 kg / 0.88 oz	
Softbox	2	Item Type: Softbox (8-Sided Octagon Shape) Interior Color: Silver Light Compatibility: Built-In Speed Ring with Godox Mount: For Godox AD300Pro / Godox AD400Pro / Godox ML60 Accepts Grids: Yes (Included)	
Bi Color LED Video Light	2	Item Type: LED Monolight Included Light Modifier: Lens Included Storage Case: Yes Photometrics at 3.3' / 1 m: 3200K: 288 fc / 3100 Lux (Unmodified) Spot Beam at 3200K: 2323 fc / 25,000 Lux (with Lens) 5600K: 344 fc / 3700 Lux (Unmodified) Spot Beam	

		at 5600K: 2750 fc / 29,600 Lux (with Lens) Color Temperature: 2800 to 6500K Color Modes: Daylight, Tungsten Color Accuracy Standard: CRI 96 TLCI 96 Dimming: App-Controlled / Built-In Dimmer 0 to 100% Front Accessory Mount: Proprietary Wireless Remote Control Type: Bluetooth Power Source: Battery (Included) USB Power (Cable Included) AC to DC Adapter (Not Included) Battery Plate Type: Proprietary (Built-In) Battery: Proprietary Rechargeable (Included) Input Power: 12 to 20 VDC at 1.5 to 5 A Fixture Mounting: 1/4"-20 Female Thread	
Air Cushioned Light Stand	2	Stand Type: General Purpose Stand Maximum Working Height: 114.2" / 290 cm Minimum Working Height: 48.4" / 123 cm Load Capacit: 22 lb / 10 kg	

		Stand/Column Top Mount: 5/8" Receiver Wheels: Optional Air Cushioned: Yes Weight: 4.4 lb / 2 kg	
Split ND Filter Set for DJI Mavic 4 Pro (2-3 Stops)	1	Filter Type: Solid ND Exposure Reduction: 2 to 3 - Stop Size: Dedicated Filter Material: Glass	
Cooling Fan for Sony Camera	2	Compatibility: Sony FX3 / FC30 / ZV-E1 / ZV-1 / a7S III / a6700 / a7C / ZV-E10 / ZV-E10 II / a7 IV / a7C II USB I/O: 1 x USB-C (Power Only) Female Input Power Source: USB DC Input Power: 4.5 to 10.8 VDC at 1 to 2 A Power Consumption: 18 W (Maximum) 5 W (Typical) Mounting: 1x Mounting Frame (8 Options) Color: Black Material of Construction: Aluminum, ABS+PC Plastic Operating Conditions: 32 to 113°F / 0 to 45°C	
Micro-HDMI to HDMI Cable	1	Interface: HDMI 2.0 Connector 1: 1x Micro-HDMI Male	

		Connector 2: 1x HDMI Male Cable Length: 13.8" / 35 cm Active/Passive: Passive Maximum Resolution Support: 3840 x 2160 at 60 Hz Materials: Jacket: Thermoplastic Elastomer (TPE) Color: Black	
COB Light	1	Item Type: 1x COB LED Monolight Included Light Modifier: 1x Reflector 1x Softbox with Removable Grid Included Storage Case: Yes Photometrics at 3.3' / 1 m: 361 fc / 3881 Lux Photometrics (with Reflector) at 3.3' / 1 m: 1609 fc / 17,317 Lux Color Temperature: 2700 to 6500K Color Modes: Daylight, Tungsten Color Accuracy Standard: CRI 95 TLCI 97 Dimming: Built-In Dimmer 0 to 100% Cooling System: Fan Built-In Flash: No Preprogrammed Effects: No Umbrella Mount: Yes	

		Front Accessory Mount: Proprietary Bowens S Wireless Remote Control Type: Bluetooth Power Source: AC to DC Adapter (Included) Battery (Included) USB Power (Cable Not Included) Inputs/Outputs: 1x Barrel / Coax Power Input 1x USB-C Power Input Battery: 1x Proprietary Rechargeable, 22.2 VDC, 15,600 mAh, 57.72 Wh (1x Included) Battery Runtime: 30-Minute Runtime at Maximum Brightness Battery Charge Time: 2.5-Hour Charge Time via USB-C Battery Charging: 1x AC to DC Adapter (Included) 1x USB-C Wall Charger (Not Included) Input Power: 24 VDC at 5 A 100 to 240 VAC, 50 / 60 Hz Included Adapter / Cable: 1x USA Type-A/B Plug to Barrel / Coax AC to DC Adapter Power Pass-Thru: No Power Consumption: 100 W (Maximum)	
--	--	--	--

		Fixture Mounting: 1x 1/4"-20 Female Thread Included Mount Adapter: 1x Swivel Mount: 5/8" Receiver to Proprietary	
Camera Strap	2	Item Type: 1 x Neck/Shoulder Strap for Camera Colour: Black Adjustable Strap: Yes Attachment Method: To Camera: Lug Ring, Loop Load Capacity: 198.4 lb / 90 kg Quick Release: Yes Materials: Nylon/Polyester/Rubber Strap Length: 59.8" / 152 cm Strap Width: 1.8" / 4.5 cm Weight: 4.9 oz / 139 g	
SD Card	3	Card Type: SDXC Storage Capacity: 128 GB Bus Type: UHS-II Speed Class: Class 10 / U3 / V90 Read Speed: Maximum: 300 MB/s Write Speed: Maximum: 260 MB/s Minimum: 90 MB/s Built-in Write-Protect Switch: Yes Operating Conditions: 32 to 158°F / 0 to 70°C	

		Storage Conditions: -13 to 185°F / -25 to 85°C	
SD Card	2	Card Type: SDXC Storage Capacity: 265GB Bus Type: UHS-II Speed Class: Class 10 / U3 / V90 Read Speed: Maximum: 300 MB/s Write Speed: Maximum: 260 MB/s Minimum: 90 MB/s Built-in Write-Protect Switch: Yes Operating Conditions: 32 to 158°F / 0 to 70°C Storage Conditions: -13 to 185°F / -25 to 85°C	
Closed Back Audio Monitor	2	Wearing Style: Dual Ear with Headband Foldable: Yes Earpiece Swivel: Yes Open/Closed-Back: Closed-Back Impedance: 38 Ohms Active Noise Cancellation: No Frequency Response: 15 Hz to 28 kHz Built-In Mic: No Audio Connector: 1x 1/8" / 3.5 mm TRS Included Adapter: 1/4" TRS Wearing Style: Dual Ear with Headband Foldable: Yes Earpiece Swivel: Yes Earpiece Design: Over-Ear (Circumaural) Open/Closed-Back: Closed-Back Sound Field: Stereo	


		Driver Type: Dynamic Driver Size: 1.8" / 45 mm Impedance: 38 Ohms Active Noise Cancellation: No Frequency Response: 15 Hz to 28 kHz Sensitivity: 99 dB Maximum Power Handling: 1600 mW Built-In Controls: No Wired Audio Connector: 1x 1/8" / 3.5 mm TRS Included Adapter: 1/4" TRS Connector Plating: Gold Cable Design: Detachable / Straight Cable Length: 9.8' / 3 m, 3.9' / 1.2 m	
Lens Cap	1	Type: Front Size: 82 mm Attachment Method: Snap-On	
SD Card Reader	3	Media Card Reader: 1x SDXC (UHS-II “312 MB/s”) 1x microSDXC (UHS-II “312 MB/s”) Host Connection: USB-C 3.1/3.2 Gen 2 via Detachable Cable Power Source: Bus Powered Operating Conditions: 32 to 104°F / 0 to 40°C up to 95% Humidity Storage Conditions: -4 to 185°F / -20 to 85°C up to 95% Humidity Enclosure Material: Aluminum	

		Dimensions: 4.1 x 2.3 x 0.5" / 103.4 x 57.7 x 12 mm	
Charger for Godox V860III-S (Charger Model VC26 Battery Charger)	1	Model: Godox VC26 USB Battery Charger Type: USB Battery Charger Purpose: Flash Battery Charging Compatible Batteries: VB26, VB26A, VB26B (Li-ion) Compatible Flash Models: Godox V1S, V1C, V1N, V1F, V1O, V1P, V1Pro, V860III, V860III-C, V860III-N, V860III-S, V860III-O, V860III-F, V850III, AD100PRO Input: DC 5V 2.0A Output: DC 8.4V 1A Interface: Type-C Indicator: LED Status Indicator (Charging Status) Charging Cable: USB charging cable not included (requires separate cable) Power Source: USB Power Adapter (5V 2.0A required)	
Clip-on Wireless Microphone	1	Wireless Technology: Digital 2.4 GHz Diversity: Non-Diversity Max Operating Range: 1115.5' / 340 m (Line of Sight) Receiver Type: 1x Camera-Mount 1x Plug-In (USB-C) Number of Audio Channels: 4 Included Transmitters: 2x Clip-On Microphone Type: 2x Built-In (Clip-On Transmitter)	


	Included Charging Case: Yes, with Integrated Battery RF Frequency Band: 2400 MHz Max Transmitters per Band: 4 Latency: 20 ms (Maximum) Encryption: No Built-In Recorder: Yes (on Transmitter via Built-In Storage) Timecode Support: Yes Receiver Mounting Options: Shoe-Mount (with Included Hardware) Receiver Antenna: 2x Internal Receiver Audio I/O: 1x 1/8" / 3.5 mm TRS Unbalanced Line Output 1x 1/8" / 3.5 mm TRS Headphone Output USB/Lightning Connectivity: 1x USB-C Male Receiver Frequency Response: 20 Hz to 20 kHz Receiver Display: LCD (Non-Backlit) Receiver Power Requirements: Battery, Bus Power (USB) Transmitter Antenna: Internal Transmitter Input Level: Microphone Transmitter Audio I/O: No Transmitter USB I/O: No Transmitter Muting: Off/On Switch Transmitter Auto-Level/Gain: Yes Transmitter Frequency Response: 20 Hz to 20 kHz Transmitter Sync Method: 2.4 GHz QPSK Transmitter Display: No	
--	--	--

		Microphone Polar Pattern: Omnidirectional Microphone Frequency Response: 20 Hz to 20 kHz Microphone Maximum SPL: 128 dB Microphone Sensitivity: -37 dBV Microphone Color: Gray Receiver Battery Type: 1x Built-In Rechargeable Receiver Battery Life: 12 Hours Transmitter Battery Type: 1x Built-In Rechargeable Transmitter Battery Life: 11 Hours Battery Charging Time: 1.5 Hours Charging Case Additional Runtime: 36 Hours Charging Case Battery: 2000 mAh Rechargeable Charging Input: USB-C AC/DC Power Adapter: No Environmental Resistance: No Receiver Dimensions: 2.1 x 1.2 x 0.9" / 54.2 x 29.5 x 22.3 mm 1.6 x 1.1 x 0.4" / 40.7 x 27 x 9.1 mm Transmitter Dimensions: 1.8 x 0.9 x 0.4" / 45.1 x 23.4 x 10.2 mm Receiver Weight: 0.8 oz / 24 g 0.2 oz / 5.9 g Transmitter Weight: 0.5 oz / 14 g	
--	--	---	--


مَدِينَةُ كُوفَا



۲



۳



4. ۛۛۛۛۛۛۛۛ



۵ رستریو



Core Interactive Flat Panel Specifications

Component	Technical Parameter	Minimum Requirement Specifications
Display & Visuals	Screen Type	Direct-lit LED Backlight with Anti-Glare/Anti-Fingerprint tempered safety glass.
	Display Size	98-inch diagonal minimum.
	Native Resolution	3840 x 2160 (4K UHD) at a minimum refresh rate of 60Hz.
	Aspect Ratio	16:9 widescreen format.
	Viewing Angle	178° horizontal and vertical minimum.
Touch Mechanics	Display Colors	1.07 Billion colors (10-bit) with automated ambient light brightness adjustments.
	Sensing Technology	High-precision Infrared (IR) sensing framework.
	Touch Points	Minimum 40 to 50 simultaneous touch points supporting multi-user collaboration.
	Writing Interface	Supports dual-color recognition, gesture erasing (palm erase), finger writing, smart charts, flowcharts, and instant whiteboard launching via integrated NFC tap module.
Core Hardware	Processor (CPU)	Flagship 8-Core configuration (Quad-core ARM Cortex-A73 + Quad-core ARM Cortex-A53 framework).
	System Memory	8GB DDR4 RAM minimum.
	Storage	128GB high-speed flash storage (ROM) minimum.
	Operating System	Android version 13.0 or higher.
	Ecosystem Licensing	MANDATORY REQUIREMENT: Google Enterprise Devices Licensing Alliance (EDLA) Certified. Panel must run a native Google Enterprise UI out of the box with official, unrestricted access to the Google Play Store , native Google Workspace apps (Drive, Docs, Sheets, Meet, Chrome), and full Google Workspace Admin Console centralized cloud device management integration.
Audio & Video	Built-in Camera	Integrated top-mounted 48MP Ultra HD AI Video Conferencing Camera featuring Auto-Framing, face-detection, and a minimum 102° distortion-free wide-angle lens.
	Microphone Array	Integrated 8-array microphone built into the touch frame; 12-meter sound pickup range, 180° wide-angle capture, AI background noise reduction, and Echo-Free full-duplex dual talk capabilities.
	Speaker System	Integrated multi-driver high-fidelity stereo soundbar system with a minimum combined output of 60W (featuring 2x 20W Front Speakers paired with an integrated 20W Low-Frequency Subwoofer).
Connectivity	Audio/Video Inputs	HDMI 2.0 In x 3 minimum, VGA In x 1, Audio In x 1.
	Audio/Video Outputs	HDMI Out x 1, Audio Out / Earphone x 1, Digital Optical SPDIF Out x 1.
	Data & Touch Interface	USB 3.0 x 4 minimum, Type-C (Full-Function supporting 4K Video, Audio, Touch-back, and minimum 65W Power Delivery) x 1, USB Touch-Back type-B ports x 2.
	Network	Dual-Band Wi-Fi (Wi-Fi 6 supported), Bluetooth version 5.3 minimum, and Gigabit Ethernet RJ45 Lan ports (In/Out switch hub functionality).

ދިވެހިރާއްޖޭގެ ސަރުކާރުގެ ސިޔާސަތުގެ ދަށުން

