

Information Sheet

Lens Mount	Sony E
Sensor Resolution	26 Megapixel
Sensor Format	APS-C
Memory Card Slot	Single Slot: SD/SDHC/SDXC

Internal Video Recording:	3840x2160 at 23.98/25/29.97/50/59.94/100/120 fps 10-Bit 4:2:2
I/O	Micro-HDMI Output 3.5mm TRS Headphone & Microphone USB-C
Display	Articulating Touchscreen LCD
Battery	NP-FZ100
Warranty	1 year

Camera Lens - Qty. 1

Lens Format Coverage	Full Frame
Focal Length	16 to 28mm
Aperture	f/2.8 to f/22
Focus Type	Autofocus
Filter Size	72 mm
Warranty	1 Year

Camera Monitor - Qty. 1

Display Size	5.5"
Video Format	Up to DCI 4K / UHD 4K
I/O	1x HDMI Output 1x HDMI Input 1x 3.5 Headphone Output 1x Barrel 2.1 mm (12V DC) Input 1x Barrel (8V DC) Output

	1x USB-C (5V DC) Input
Media Slot	SD Card for LUT Upload
Battery	1x L-Series/LP-E6 Combo Mount
Mounting	Bottom/Left/Right 1x 1/4"-20 Female

Camera Cage - Qty. 1

Camera Compatibility	Sony A74
Accessory Mounting	Cage Multiple 1/4"-20 Female Thread Multiple Anti-Twist 3/8"-16 Female Thread
Tripod Mounting	Built-In Arca-Type Plate
Rail Mounting	1x NATO R

Camera Cage Handle - Qty. 1

Attachment Method	ARRI-Style Anti-Twist Mount
Accessory Mounting	3x Anti-Twist 1/4"-20 Thread 1x Built-In Cold Shoe 1x NATO Rail Clamp

Camera Strap - Qty.3

Type	Shoulder Strap
Attachment Method	Quick Release Lug Ring, Loop

Length	152 cm
Materials	Nylon/ Polyester/ Rubber
Capacity	90 kg

Camera Bag - Qty. 1

Volume	25 L
Interior Type	Insert with Adjustable Dividers (Hook & Loop)
Closure Type	Zipper
Water Resistance	Included Rain Cover

Memory Card - Qty. 2

Card Type	SDXC
Capacity	128 GB
Bus Type	UHS-II
Speed Class	Class 10/U3/V90

Memory Card Reader - Qty. 2

Media Type	1x SDXC (UHS-II [312 MB/s]) 1x microSDXC (UHS-II [312 MB/s])
I/O	USB-C 3.1/3.2 Gen 2 Female

Power	USB Bus Power
Build	Aluminum

Tripod - Qty. 2

Mounting	1/4"-20 Screw (Quick Release Plate: Arca-Type)
Head Type	Ball Head
Primary Material	Carbon Fiber
Working Height	Maximum: 141 cm Minimum: 45 cm
Load Capacity	8 kg

Tripod Accessory - Smartphone Holder - Qty. 1

Compatible Device Width	6.1 to 9.4 cm
Tripod Mount	Arca-Type Plate with 1x 1/4"-20 Female Thread 1x 3/8"-16 Female Thread
Accessory Mounting	Cold Shoe
Material	Aluminum

In-Ear Monitor Headphones - Qty. 4

Wearing Style	Dual Wired Earbuds
Earpiece Design	In-Ear Closed-Back
Driver Quality	Dynamic

	12 Ohms Impedance 20 Hz to 20 KHz Response
Connectivity	3.5 mm TRS Right-Angled (Gold Plated)
Cable Design	Detachable/ Straight
Audio Connector to Earpiece	A2DC
Cable Length	1.6 m

Cable Reel - Qty.10

Dimensions	Center Hub Diameter: 4.75" / 12.1 cm Center Hub Depth: 5" / 12.7 cm Outer Hub Diameter: 10.75" / 27.3 cm Overall Reel Height: 15" / 38.1 cm Feed-Through Hole Diameter: 0.47" / 1.2 cm Overall: 15 x 12 x 10" / 38.1 x 30.5 x 25.4 cm
Material	Steel Frame Thermo-plastic Core

3G-SDI Repeater - Qty.3

Input	1x SDI on BNC
Output	1x SDI on BNC
SDI Format	3G-SDI (SMPTE 424M / SMPTE 425M) HD-SDI (SMPTE 292M) SD-SDI (SMPTE 259M)
Transmission Distance	Over RG6 Cable: 3G-SDI: 328 ft (100 m)

	HD-SDI: 557 ft (170 m) SD-SDI: 1312 ft (400 m) Over RG59 Cable: 3G-SDI: 282 ft (86 m) HD-SDI: 393 ft (120 m) SD-SDI: 918 ft (280 m)
Power Source	Included Power Adapter: 100 - 240 VAC / DC (6 - 15 V)

Dual-Arm Monitor Mount - Qty.8

Compatibility	Screen Sizes 17 to 35" Weighs up to 32.5 lb / 14.7 kg
VESA Mounting	75 x 75 to 100 x 100 mm
Mounting	Desk Clamp: Up to 3.1" / 8 cm
Extension	Arm: Up to 21.1" / 53.6 cm
Control	Swivel, Tilt and Rotation

Colour Accurate Monitor - Qty.8

Display Size	23.8" 2560 x 1440
Panel Type	IPS LCD HDR10

	75 Hz Adaptive-Sync 100% sRGB Coverage
I/O	1x DisplayPort 1.4 1x HDMI 2.0 3x USB-A 1x USB-C with Power Delivery Built in Speakers

Under-Desk PC Mount - Qty.8

Compatibility	Minimum Case Height - 42cm Minimum Case Width - 14cm Maximum Height - 57cm
Mounting	Screws

Portable USB Drive - Qty.4

Capacity	256 GB
Connection	Dual-Sided USB-C & USB-A
Transfer Speed	Up to 400 MB/s

Multi-Socket Power Strip - Qty.2

AC Outlets	6x universal Sockets
USB Ports	1x USB-A 1x USB-C Power Delivery
Total Output	2,500W / 10A
Cord	2m (Type G Plug)
Safety	Surge Protection Master On/Off Switch

Multi-Socket Power Strip - Qty.2

AC Outlets	6x universal Sockets
USB Ports	1x USB-A 1x USB-C Power Delivery
Total Output	2,500W / 10A
Cord	1.5m (Type G Plug)
Safety	Surge Protection Master On/Off Switch

Universal Camera Cage - Qty.1

Construction	Aluminum
Accessory Mounting	Multiple 1/4"-20 & 3/8"-16 threads on top & sides, cold shoe
Camera Mounting	1/4"-20 screw
Tripod Mounting	1/4"-20 & 3/8"-16 threaded holes
Compatibility	Universal – height-adjustable to fit various camera sizes

Double Head Stud - Qty.10

Thread Size	1/4"-20 male thread on both ends
Length	Approx. 20mm

Camcorder AC Adapter - Qty. 3

AC Adapter/DC Coupler Compatibility	Sony Camera via Direct Plug into Camera
AC Adapter/DC Coupler Included Adapter / Cable	1x IEC Female to Proprietary Cable • 100 to 240 VAC, 50 / 60 Hz • 8 VDC at 1.5 A 1x USA Type-A/B Plug to IEC Male AC To DC Adapter

Sliding Balance Plate for Tripod - Qty.3

Mounting	1x 1/4"-20 Male 1x 3/8"-16 Male
Compatibility	For Magnus Rex VT-5000/VT-6000 Tripods